



Technical Data

Model		AJ- 22P
Prime power	kva	20
	kw	16
Standby power	kva	22
	kw	18
Rated voltage line to line	V	230/400
Rated current	A	28,8
Maximun sound level	dB@7m	70

Engine-Perkins

Model		404-22G
Aspiration		Four-stroke, water-cooled, In line, Natural apirated
Fuel system		Direct injection
No. cylinders		4
Displacement	L	2,216
Bore*Stroke	mm	84x100
Compression ratio		23.3:1
Rated speed	r/min	1500
Governor		Mechanical
Engine size	mm	840x497x946
Engine wet weight	kg	242
Fire order		1-3-4-2
Start Motor	V	12
Rotation		Anti-clockwise, viewed on the flywheel

Air Inlet

Air inlet	mounted air filter
-----------	--------------------

Fuel System

mechanical governor	cassette type fuel pump
fuel filter	split element type

Fuel System

110% load(Standby power)	L/h	6,9
100% load(Prime power)	L/h	6,2
75% load(Prime power)	L/h	4,8
50% load(Prime power)	L/h	3,5
Fuel capacity	L	55

Lubrication System

Oil capacity	L	10,6
--------------	---	------

Cooling System

Total coolant capacity	L	7
------------------------	---	---

Standard Features

Engine(Perkins ENGINE)	●
Radiator 50°C max, fans are driven by belt	●
12V charge alternator	●
Alternator: single bearing alternator IP23	●
insulation class H/H	●
Standard auto control system	●
Main line circuit breaker / ACB	●
Base fuel tank	●
12V batteries, rac and cable	●
Exhaust system(Ripple flex exhaust pipe)	●
Exhaust siphon, flange, muffler	●
User manual	●
Battery charge	●

Options

Water heater	○
Alternator heater	○
One set of air filter, fuel filter, oil filter	○
PMG	○
Water oil separator	○
Daily fuel tank	○
Remote control panel	○
Automatic transfer switch/ATS	○
Switch box	○
Standard: ●	Options:○

Alternator

Model		TAL-40-F
Alternator Brand		Leroy Somer
Phase		3
Voltage	V	230/400
Wiring Type		12 wires
Bearing		1
Power factor		0,8
Frequency	Hz	50
Prime power	KVA	20
Exciter Type		Brushless, self-excitation
Voltage regulation	%	±0.5
Protection Grade		IP 23
Insulation grade		H


Controller-Deepsea

Model DSE 6120

7 configurable digital inputs
Built-in governor and AVR control
Base load (kW export) functionality
Mains (utility) de-coupling protection
Generator power (kW, kVA) monitoring
Overload (kW & kV Ar) protection
Emergency stop
Start failure



Unit Dimensions(Basic unit)

		
L*W*H	mm	2000x850x1250
Weight	kg	798

Warranty

Perkins Engine

12 months from date of purchase or 1000 hours.

Generator

12 months from date of purchase or 1000 hours



YOUR INTERNATIONAL PARTNER FOR
NEW AND USED GENERATOR SETS